

DOME Series

DOWNLIGHT




D200

Downlight



White Black

Drawing



Order Options

24W 3300 lm

Code	Size	System LM	LED Voltage	LED Current	LED W	System W	CRI	CCT	Beam
D200-24W-830-18	Ø216*131mm	3300 lm	36 V	700mA	24W	26W	83	3000K	18°
D200-24W-840-18	Ø216*131mm	3500 lm	36 V	700mA	24W	26W	83	4000K	18°
D200-24W-830-30	Ø216*131mm	3400 lm	36 V	700mA	24W	26W	83	3000K	30°
D200-24W-840-30	Ø216*131mm	3600 lm	36 V	700mA	24W	26W	83	4000K	30°
D200-24W-830-65	Ø216*131mm	2900 lm	36 V	700mA	24W	26W	83	3000K	65°
D200-24W-840-65	Ø216*131mm	3100 lm	36 V	700mA	24W	26W	83	4000K	65°

Remark: X=F (ON-OFF) X=P (Phase Dim) X=A (1-10V Dim) X=D (DALI Dim) X=N (Without Driver)

36W 4800 lm

Code	Size	System LM	LED Voltage	LED Current	LED W	System W	CRI	CCT	Beam
D200-36W-830-18	Ø216*131mm	4800 lm	36 V	1050mA	36W	40W	83	3000K	18°
D200-36W-840-18	Ø216*131mm	5100 lm	36 V	1050mA	36W	40W	83	4000K	18°
D200-36W-830-30	Ø216*131mm	4900 lm	36 V	1050mA	36W	40W	83	3000K	30°
D200-36W-840-30	Ø216*131mm	5200 lm	36 V	1050mA	36W	40W	83	4000K	30°
D200-36W-830-65	Ø216*131mm	4200 lm	36 V	1050mA	36W	40W	83	3000K	65°
D200-36W-840-65	Ø216*131mm	4500 lm	36 V	1050mA	36W	40W	83	4000K	65°

Remark: X=F (ON-OFF) X=P (Phase Dim) X=A (1-10V Dim) X=D (DALI Dim) X=N (Without Driver)

51W 5600 lm

Code	Size	System LM	LED Voltage	LED Current	LED W	System W	CRI	CCT	Beam
D200-51W-830-18	Ø216*131mm	5900 lm	36 V	1400mA	51W	55W	83	3000K	18°
D200-51W-840-18	Ø216*131mm	6300 lm	36 V	1400mA	51W	55W	83	4000K	18°
D200-51W-830-30	Ø216*131mm	6300 lm	36 V	1400mA	51W	55W	83	3000K	30°
D200-51W-840-30	Ø216*131mm	6700 lm	36 V	1400mA	51W	55W	83	4000K	30°
D200-51W-830-65	Ø216*131mm	5200 lm	36 V	1400mA	51W	55W	83	3000K	65°
D200-51W-840-65	Ø216*131mm	5600 lm	36 V	1400mA	51W	55W	83	4000K	65°

Remark: X=F (ON-OFF) X=P (Phase Dim) X=A (1-10V Dim) X=D (DALI Dim) X=N (Without Driver)