



START Series
DOWNLIGHT / Adjustable



SRA125
Downlight



Drawing



Order Options

18W 1400Lm-1700Lm		CITIZEN						
Code	Size	System LM	LED Voltage	LED W	System W	CRI	CCT	Beam
SRA125-CC930L20S-X	Ø137*159mm	1600 lm	36 V	18 W	21 W	90	3000K	20°
SRA125-CC940L20S-X	Ø137*159mm	1700 lm	36 V	18 W	21 W	90	4000K	20°
SRA125-CC930L35S-X	Ø137*159mm	1600 lm	36 V	18 W	21 W	90	3000K	35°
SRA125-CC940L35S-X	Ø137*159mm	1700 lm	36 V	18 W	21 W	90	4000K	35°
SRA125-CC930L50S-X	Ø137*159mm	1400 lm	36 V	18 W	21 W	90	3000K	50°
SRA125-CC940L50S-X	Ø137*159mm	1500 lm	36 V	18 W	21 W	90	4000K	50°

Remark: X=F (ON-OFF) X=P (Phase Dim) X=A (1-10V Dim) X=D (DALI Dim) X=N (Without Driver)

25W 1900Lm-2300Lm		CITIZEN						
Code	Size	System LM	LED Voltage	LED W	System W	CRI	CCT	Beam
SRA125-CD930L20S-X	Ø137*159mm	2200 lm	36 V	25 W	28 W	90	3000K	20°
SRA125-CD940L20S-X	Ø137*159mm	2300 lm	36 V	25 W	28 W	90	4000K	20°
SRA125-CD930L35S-X	Ø137*159mm	2200 lm	36 V	25 W	28 W	90	3000K	35°
SRA125-CD940L35S-X	Ø137*159mm	2300 lm	36 V	25 W	28 W	90	4000K	35°
SRA125-CD930L50S-X	Ø137*159mm	1900 lm	36 V	25 W	28 W	90	3000K	50°
SRA125-CD940L50S-X	Ø137*159mm	2000 lm	36 V	25 W	28 W	90	4000K	50°

Remark: X=F (ON-OFF) X=P (Phase Dim) X=A (1-10V Dim) X=D (DALI Dim) X=N (Without Driver)