


START Series
DOWNLIGHT / Adjustable




SRA45

Downlight



Drawing



Order Options

4W 350lm-380lm		CREE							
Code	Size	System LM	LED Voltage	LED Current	System W	CRI	CCT	Beam	
SRA45-EY930L18M-X	Ø55*60mm	350 lm	12 V	350mA	6 W	90	3000K	18°	
SRA45-EY940L18M-X	Ø55*60mm	380 lm	12 V	350mA	6 W	90	4000K	18°	
SRA45-EY930L24M-X	Ø55*60mm	350 lm	12 V	350mA	6 W	90	3000K	24°	
SRA45-EY940L24M-X	Ø55*60mm	380 lm	12 V	350mA	6 W	90	4000K	24°	
SRA45-EY930L35M-X	Ø55*60mm	350 lm	12 V	350mA	6 W	90	3000K	35°	
SRA45-EY940L35M-X	Ø55*60mm	380 lm	12 V	350mA	6 W	90	4000K	35°	
SRA45-EY930L50M-X	Ø55*60mm	350 lm	12 V	350mA	6 W	90	3000K	50°	
SRA45-EY940L50M-X	Ø55*60mm	380 lm	12 V	350mA	6 W	90	4000K	50°	

Remark: X=F (ON-OFF) X=P (Phase Dim) X=A (1-10V Dim) X=D (DALI Dim) X=N (Without Driver)