



START Series
DOWNLIGHT / Adjustable



SSA100

Downlight



13W 1100Lm-1300Lm CITIZEN

Code	Size	System LM	LED Voltage	LED W	System W	CRI	CCT	Beam
SSA100-CB930L20S-X	Φ107*131mm	1100 lm	36 V	13 W	15 W	90	3000K	20°
SSA100-CB940L20S-X	Φ107*131mm	1200 lm	36 V	13 W	15 W	90	4000K	20°
SSA100-CB930L30S-X	Φ107*131mm	1200 lm	36 V	13 W	15 W	90	3000K	30°
SSA100-CB940L30S-X	Φ107*131mm	1300 lm	36 V	13 W	15 W	90	4000K	30°
SSA100-CB930L40S-X	Φ107*131mm	1200 lm	36 V	13 W	15 W	90	3000K	40°
SSA100-CB940L40S-X	Φ107*131mm	1300 lm	36V	13 W	15 W	90	4000K	40°
SSA100-CB930L45S-X	Φ107*131mm	1100 lm	36 V	13 W	15 W	90	3000K	45°
SSA100-CB940L45S-X	Φ107*131mm	1200 lm	36 V	13 W	15 W	90	4000K	45°

Remark: X=F (ON-OFF) X=P (Phase Dim) X=A (1-10V Dim) X=D (DALI Dim) X=N (Without Driver)

18W 1600Lm-1800Lm CITIZEN

Code	Size	System LM	LED Voltage	LED W	System W	CRI	CCT	Beam
SSA100-CC930L20S-X	Φ107*131mm	1600 lm	36 V	18 W	21 W	90	3000K	20°
SSA100-CC940L20S-X	Φ107*131mm	1700 lm	36 V	18 W	21 W	90	4000K	20°
SSA100-CC930L30S-X	Φ107*131mm	1700 lm	36 V	18 W	21 W	90	3000K	30°
SSA100-CC940L30S-X	Φ107*131mm	1800 lm	36 V	18 W	21 W	90	4000K	30°
SSA100-CC930L40S-X	Φ107*131mm	1700 lm	36 V	18 W	21 W	90	3000K	40°
SSA100-CC940L40S-X	Φ107*131mm	1800 lm	36 V	18 W	21 W	90	4000K	40°
SSA100-CC930L45S-X	Φ107*131mm	1600 lm	36 V	18 W	21 W	90	3000K	45°
SSA100-CC940L45S-X	Φ107*131mm	1700 lm	36 V	18 W	21 W	90	4000K	45°

Remark: X=F (ON-OFF) X=P (Phase Dim) X=A (1-10V Dim) X=D (DALI Dim) X=N (Without Driver)

7W 500Lm-550Lm CREE

Code	Size	System LM	LED Voltage	LED W	System W	CRI	CCT	Beam
SSA100-CA930L10S-X	Φ107*131mm	500 lm	36 V	7 W	9 W	90	3000K	10°
SSA100-CA940L10S-X	Φ107*131mm	550 lm	36 V	7 W	9 W	90	4000K	10°

25W 2100Lm-2300Lm CITIZEN

Code	Size	System LM	LED Voltage	LED W	System W	CRI	CCT	Beam
SSA100-CD930L20S-X	Φ107*158mm	2100 lm	36V	25W	28W	90	3000K	20°
SSA100-CD940L20S-X	Φ107*158mm	2200 lm	36V	25W	28W	90	4000K	20°
SSA100-CD930L36S-X	Φ107*158mm	2200 lm	36V	25W	28W	90	3000K	36°
SSA100-CD940L36S-X	Φ107*158mm	2300 lm	36V	25W	28W	90	4000K	36°
SSA100-CD930L50S-X	Φ107*158mm	2200 lm	36V	25W	28W	90	3000K	50°
SSA100-CD940L50S-X	Φ107*158mm	2300 lm	36V	25W	28W	90	4000K	50°

Remark: X=F (ON-OFF) X=P (Phase Dim) X=A (1-10V Dim) X=D (DALI Dim) X=N (Without Driver)