


START Series

DOWNLIGHT / Adjustable




SSA150

Downlight



Drawing



Order Options



25W 1700Lm-2500Lm

CITIZEN

Code	Size	System LM	LED Voltage	LED W	System W	CRI	CCT	Beam
SSA150-CD930L20S-X	162*190mm	2400 lm	36 V	25 W	28 W	90	3000K	20°
SSA150-CD940L20S-X	162*190mm	2500 lm	36 V	25 W	28 W	90	4000K	20°
SSA150-CD930L35S-X	162*190mm	2400 lm	36 V	25 W	28 W	90	3000K	35°
SSA150-CD940L35S-X	162*190mm	2500 lm	36 V	25 W	28 W	90	4000K	35°
SSA150-CD930L50S-X	162*190mm	1700 lm	36 V	25 W	28 W	90	3000K	50°
SSA150-CD940L50S-X	162*190mm	1800 lm	36 V	25 W	28 W	90	4000K	50°

Remark: X=F (ON-OFF) X=P (Phase Dim) X=A (1-10V Dim) X=D (DALI Dim) X=N (Without Driver)

38W 2600Lm-3300Lm

CITIZEN

Code	Size	System LM	LED Voltage	LED W	System W	CRI	CCT	Beam
SSA150-CF930L20S-X	162*190mm	3200 lm	36 V	38 W	42 W	90	3000K	20°
SSA150-CF940L20S-X	162*190mm	3300 lm	36 V	38 W	42 W	90	4000K	20°
SSA150-CF930L35S-X	162*190mm	3200 lm	36 V	38 W	42 W	90	3000K	35°
SSA150-CF940L35S-X	162*190mm	3300 lm	36 V	38 W	42 W	90	4000K	35°
SSA150-CF930L50S-X	162*190mm	2600 lm	36 V	38 W	42 W	90	3000K	50°
SSA150-CF940L50S-X	162*190mm	2700 lm	36 V	38 W	42 W	90	4000K	50°

Remark: X=F (ON-OFF) X=P (Phase Dim) X=A (1-10V Dim) X=D (DALI Dim) X=N (Without Driver)