


START Series

DOWNLIGHT / FIXED




SSF150

Downlight



Drawing



Order Options

25 W 1900lm-2000lm		CITIZEN						
Code	Size	System LM	LED Voltage	LED Current	System W	CRI	CCT	Beam
SSF150-CD930R28S-X	159x191mm	1900 lm	36 V	700mA	28W	90	3000K	28°
SSF150-CD940R28S-X	159x191mm	2000 lm	36 V	700mA	28W	90	4000K	28°
SSF150-CD930R32S-X	159x191mm	1900 lm	36 V	700mA	28W	90	3000K	32°
SSF150-CD940R32S-X	159x191mm	2000 lm	36 V	700mA	28W	90	4000K	32°
SSF150-CD930R50S-X	159x191mm	1900 lm	36 V	700mA	28W	90	3000K	50°
SSF150-CD940R50S-X	159x191mm	2000 lm	36 V	700mA	28W	90	4000K	50°

Remark: X=F (ON-OFF) X=P (Phase Dim) X=A (1-10V Dim) X=D (DALI Dim) X=N (Without Driver)

38 W 2700lm-2900lm		CITIZEN						
Code	Size	System LM	LED Voltage	LED Current	System W	CRI	CCT	Beam
SSF150-CF930R28S-X	159x191mm	2700 lm	36 V	1050mA	42W	90	3000K	28°
SSF150-CF940R28S-X	159x191mm	2900 lm	36 V	1050mA	42W	90	4000K	28°
SSF150-CF930R32S-X	159x191mm	2700 lm	36 V	1050mA	42W	90	3000K	32°
SSF150-CF940R32S-X	159x191mm	2900 lm	36 V	1050mA	42W	90	4000K	32°
SSF150-CF930R50S-X	159x191mm	2700 lm	36 V	1050mA	42W	90	3000K	50°
SSF150-CF940R50S-X	159x191mm	2900 lm	36 V	1050mA	42W	90	4000K	50°

Remark: X=F (ON-OFF) X=P (Phase Dim) X=A (1-10V Dim) X=D (DALI Dim) X=N (Without Driver)