

START Series

DOWNLIGHT / FIXED




TRF150

Downlight



Drawing



Order Options

25 W 1900lm-2000lm

CITIZEN

Code	Size	System LM	LED Voltage	LED Current	System W	CRI	CCT	Beam
TRF150-CD930R28S-X	Ø162*190mm	1900 lm	36 V	700mA	28W	90	3000K	28°
TRF150-CD940R28S-X	Ø162*190mm	2000 lm	36 V	700mA	28W	90	4000K	28°
TRF150-CD930R32S-X	Ø162*190mm	1900 lm	36 V	700mA	28W	90	3000K	32°
TRF150-CD940R32S-X	Ø162*190mm	2000 lm	36 V	700mA	28W	90	4000K	32°
TRF150-CD930R50S-X	Ø162*190mm	1900 lm	36 V	700mA	28W	90	3000K	50°
TRF150-CD940R50S-X	Ø162*190mm	2000 lm	36 V	700mA	28W	90	4000K	50°

Remark: X=F (ON-OFF) X=P (Phase Dim) X=A (1-10V Dim) X=D (DALI Dim) X=N (Without Driver)

38 W 2700lm-2900lm

CITIZEN

Code	Size	System LM	LED Voltage	LED Current	System W	CRI	CCT	Beam
TRF150-CF930R28S-X	Ø78*98mm	2700 lm	36 V	1050mA	42W	90	3000K	28°
TRF150-CF940R28S-X	Ø78*98mm	2900 lm	36 V	1050mA	42W	90	4000K	28°
TRF150-CF930R32S-X	Ø78*98mm	2700 lm	36 V	1050mA	42W	90	3000K	32°
TRF150-CF940R32S-X	Ø78*98mm	2900 lm	36 V	1050mA	42W	90	4000K	32°
TRF150-CF930R50S-X	Ø78*98mm	2700 lm	36 V	1050mA	42W	90	3000K	50°
TRF150-CF940R50S-X	Ø78*98mm	2900 lm	36 V	1050mA	42W	90	4000K	50°

Remark: X=F (ON-OFF) X=P (Phase Dim) X=A (1-10V Dim) X=D (DALI Dim) X=N (Without Driver)