




FAIRY B Garden Light





Order Options

FAIRY S100 CV											
Code	System LM	LED W	System W	Input Voltage	CRI	ССТ	Beam				
FAIRY S100 B CV-82230	260 /390lm	4W	5W	24V DC	80	2200/3000K	130°				

FAIRY S100 HV											
Code	System LM	LED W	System W	Input Voltage	CRI	ССТ	Beam				
FAIRY S100 B HV-82230	300 /460lm	6W	7W	220-240VAC	80	2200/3000K	130°				



Features

- Modular designed pathway light with IP66 waterproof rating,perfect for outdoor use
- TWist&Lock covers are interchangeable, styles can be custom made
- Press button for CCT changeable, warm 2200K or cozy 3000K
- Extension poles are available with shrubbery growing
- · Multiple installation accessories; Pole, Spike or base mounting
- Triple layer coating, ensuring over 1000hours of salt mist test, suitable for seaside installations
- 24VDC or 220-240VAC input are optional
- Wider light distribution 120° achieved by advanced lens design
- Invisible screws for esthetic appeal
- 5 years warranty

Specifications

- Input Voltage:24VDC/220-240VAC
- · Beam angle:130°
- · Physical: Die-casting, Powder coating

Type



Accessory



Pole spike

For soft soil



For hard soil





MT03 Base

For wood or concrete

Light distribution





EP300

Extension Pole 300mm

Length can be tailored