



START Series
DOWNLIGHT / Adjustable



SRA68
Downlight



Drawing



7.5 W 600lm-650lm		CITIZEN						
Code	Size	System LM	LED Voltage	LED W	System W	CRI	CCT	Beam
SRA68-CA930L20S-X	Φ78*98mm	600 lm	31 V	7.5W	9 W	90	3000K	24°
SRA68-CA940L20S-X	Φ78*98mm	650 lm	31 V	7.5W	9 W	90	4000K	24°
SRA68-CA930L40S-X	Φ78*98mm	600 lm	31 V	7.5W	9 W	90	3000K	40°
SRA68-CA940L40S-X	Φ78*98mm	650 lm	31 V	7.5W	9 W	90	4000K	40°
SRA68-CA930R55S-X	Φ78*98mm	500 lm	31 V	7.5W	9 W	90	3000K	55°
SRA68-CA940R55S-X	Φ78*98mm	550 lm	31 V	7.5W	9 W	90	4000K	55°

Remark: X=F (ON-OFF) X=P (Phase Dim) X=A (1-10V Dim) X=D (DALI Dim) X=N (Without Driver)

11 W 800lm-850lm		CITIZEN						
Code	Size	System LM	LED Voltage	LED W	System W	CRI	CCT	Beam
SRA68-CB930L20S-X	Φ78*98mm	800 lm	31 V	11 W	13 W	90	3000K	24°
SRA68-CB940L20S-X	Φ78*98mm	850 lm	31 V	11 W	13 W	90	4000K	24°
SRA68-CB930L40S-X	Φ78*98mm	800 lm	31 V	11 W	13 W	90	3000K	40°
SRA68-CB940L40S-X	Φ78*98mm	850 lm	31 V	11 W	13 W	90	4000K	40°
SRA68-CB930R55S-X	Φ78*98mm	650 lm	31 V	11 W	13 W	90	3000K	55°
SRA68-CB940R55S-X	Φ78*98mm	700 lm	31 V	11 W	13 W	90	4000K	55°

Remark: X=F (ON-OFF) X=P (Phase Dim) X=A (1-10V Dim) X=D (DALI Dim) X=N (Without Driver)

8.5 W 480lm-500lm		CREE ⇄						
Code	Size	System LM	LED Voltage	LED W	System W	CRI	CCT	Beam
SRA68-EA930L10S-X	Φ78*98mm	480 lm	12V	8.5 W	10W	90	3000K	10°
SRA68-EA940L10S-X	Φ78*98mm	500 lm	12V	8.5 W	10W	90	4000K	10°

Remark: X=F (ON-OFF) X=P (Phase Dim) X=A (1-10V Dim) X=D (DALI Dim) X=N (Without Driver)