

START Series


DOWNLIGHT / Adjustable



TSA68 Downlight



Drawing



Order Options



| 7.5 W 600lm-650lm | | CITIZEN | | | | | | |
|-------------------|---------|-----------|-------------|-------|----------|-----|-------|------|
| Code | Size | System LM | LED Voltage | LED W | System W | CRI | CCT | Beam |
| TSA68-CA930L20S-X | 78*98mm | 600 lm | 31 V | 7.5 W | 9 W | 90 | 3000K | 24° |
| TSA68-CA940L20S-X | 78*98mm | 650 lm | 31 V | 7.5 W | 9 W | 90 | 4000K | 24° |
| TSA68-CA930L40S-X | 78*98mm | 600 lm | 31 V | 7.5 W | 9 W | 90 | 3000K | 40° |
| TSA68-CA940L40S-X | 78*98mm | 650 lm | 31 V | 7.5 W | 9 W | 90 | 4000K | 40° |
| TSA68-CA930R55S-X | 78*98mm | 500 lm | 31 V | 7.5 W | 9 W | 90 | 3000K | 55° |
| TSA68-CA940R55S-X | 78*98mm | 550 lm | 31 V | 7.5 W | 9 W | 90 | 4000K | 55° |

Remark: X=F (ON-OFF) X=P (Phase Dim) X=A (1-10V Dim) X=D (DALI Dim) X=N (Without Driver)

| 11 W 800lm-850lm | | CITIZEN | | | | | | |
|-------------------|---------|-----------|-------------|-------|----------|-----|-------|------|
| Code | Size | System LM | LED Voltage | LED W | System W | CRI | CCT | Beam |
| TSA68-CB930L20S-X | 78*98mm | 800 lm | 31 V | 11 W | 13 W | 90 | 3000K | 24° |
| TSA68-CB940L20S-X | 78*98mm | 850 lm | 31 V | 11 W | 13 W | 90 | 4000K | 24° |
| TSA68-CB930L40S-X | 78*98mm | 800 lm | 31 V | 11 W | 13 W | 90 | 3000K | 40° |
| TSA68-CB940L40S-X | 78*98mm | 850 lm | 31 V | 11 W | 13 W | 90 | 4000K | 40° |
| TSA68-CB930R55S-X | 78*98mm | 650 lm | 31 V | 11 W | 13 W | 90 | 3000K | 55° |
| TSA68-CB940R55S-X | 78*98mm | 700 lm | 31 V | 11 W | 13 W | 90 | 4000K | 55° |

Remark: X=F (ON-OFF) X=P (Phase Dim) X=A (1-10V Dim) X=D (DALI Dim) X=N (Without Driver)

| 8.5 W 480lm-500lm | | CREE | | | | | | |
|-------------------|---------|-----------|-------------|-------------|----------|-----|-------|------|
| Code | Size | System LM | LED Voltage | LED Current | System W | CRI | CCT | Beam |
| TSA68-EA930L10S-X | 78*98mm | 480 lm | 12 V | 700mA | 10 W | 90 | 3000K | 10° |
| TSA68-EA940L10S-X | 78*98mm | 500 lm | 12 V | 700mA | 10 W | 90 | 4000K | 10° |